

# Standard Series – proven in practice

Fully ground core drills, extra long version, metric.

Standard core drill KEL  
Cutting depth 110 mm Weldon shank 19 mm (3/4")



Order No.	ø - mm	Order No.	ø - mm
KEL 020	20	KEL 036	36
KEL 021	21	KEL 037	37
KEL 022	22	KEL 038	38
KEL 023	23	KEL 039	39
KEL 024	24	KEL 040	40
KEL 025	25	KEL 041	41
KEL 026	26	KEL 042	42
KEL 027	27	KEL 043	43
KEL 028	28	KEL 044	44
KEL 029	29	KEL 045	45
KEL 030	30	KEL 046	46
KEL 031	31	KEL 047	47
KEL 032	32	KEL 048	48
KEL 033	33	KEL 049	49
KEL 034	34	KEL 050	50
KEL 035	35		



**The function of the two-piece ejector pin:**

The lower part of the pin is removed in order to fully utilize the full cutting depth of 110 mm of a KEL core drill!

Ejector pin for KEL with 6.35 mm bore diameter



For KEL with bore diameter 6.35 mm (old version)

Order No.	Drilling range
ZAK 175	ø 20 - 50 mm

Ejector pin for KEL mit 8 mm bore diameter



For KEL with bore diameter 8 mm (new version)

Order No.	Version	Drilling range
ZAK 275	two-part	ø 20 - 50 mm